

IC650 Industrial Battery Charger



- *Universal IEC320/C14 connector AC receptacle
- *Universal DC output terminals for customizable OEM DC cables
- *Battery temperature sensor and vehicle interlock signals
- *Sealed USB 2.0 host port (Type A) with dust cover
- *AC source, battery status, charging, alarm, and fault status indicators
- *Charge profile and alarm/fault codes numeric display
- *Field programmable with up to 25 user-selectable charge profiles

MODELS

940-0001 24 VDC / 27.1 amp

940-0002 36 VDC / 18.1 amp

940-0003 48 VDC / 13.5 amp



- *Includes all BASE CONFIGURATION features
- *CANbus (CANopen CiA 418/419)
- *Remote tri-color status indicator
- *Battery temperature sensor
- *Vehicle interlock (NO and NC dry contacts)

940-0004 24 VDC / 27.1 amp

940-0005 36 VDC / 18.1 amp

940-0006 48 VDC / 13.5 amp

MODELS

AC CORDS

AC CORD



10' (3M) NEMA 5-15

475-0349



6.5' (2M) Locking • Sealed NEMA 5-15

475-0406



10' (3M) **NEMA 5-15**

475-0410



10' (3M) Locking • Sealed SCHUKO





1.5' (0.45M) Locking • Sealed **PIGTAIL**

BATTERY SYSTEMS

The Single Source Solution!

DC HARNESS

475-0351



6' (1.8M) 3/8" Ring Terminal

475-0353



8'(2.4M)

475-0409



475-0354



8'(2.4M) APP - SB175 Grey



475-0379

2' (0.6M) APP - SB175 Black (Universal)

SIGNAL HARNESS





10' (3M)

475-0357



6' (1.8M)

475-0358



1' (0.6M) 14 CCT - PIGTAIL

475-0359



6' (1.8M) Isolated BTS · Remote LED 10 CCT - PIGTAIL

ACCESSORIES

900-0111



900-0112



GP-BRACKET



426-0062



Breakaway Clamp

SERVICE ITEMS

900-0058



10' (3M) Remote LED - Shielded **Bare Wires**

900-0061



Remote LED Label (10 Pack)

900-0056



10' (3M) Isolated Temp Sensor Shielded · Bare Wires

900-0002



Thermistor Repair Kit